



ZPMV2.E352816 Wiring, Printed - Component

If you notice a change to your ZPMV2 Listing Card, click [here](#) to learn more.

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

KINGFORD PCB ELECTRONICS CO LTD

E352816

FLAT RM 704 7F

BRIGHT WAY TOWER


33 MONG KOK ROAD MONG KOK KL

HONG KONG, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max			Max			Meets UL796 DSR	C T I
	Min	Edge			Area	Solder	Oper	Flame				
	mm(in)	mm(in)			Diam	Limits	Temp	Class				
Multilayer printed wiring boards.												
KF-4M	0.10 (0.004)	0.26 (0.010)	17 (0.67) Int:68	DS	50.8 (2.0)	288	10	130	V-0	All	*	
KF-5M	0.10 (0.004)	0.10 (0.004)	17 (0.67) Int:70	DS	25.4 (1.0)	260	10	130	V-0	All	*	
M1	0.1 (0.004)	0.26 (0.010)	17 (0.67) Int:68	DS	25.4 (1.0)	288	10	130	V-0	All	*	
M2 (%)	0.2 (0.008)	0.2 (0.008)	17 (0.67) Int:140	DS	38 (1.5)	288	10	130	V-0	All	*	
Single layer Metal Base Printed Wiring Board.												
AL	0.15 (0.006)	0.2 (0.008)	17 (0.67)	SS	50.8 (2.0)	288	20	110	V-0	All	0	
Single layer metal base printed wiring boards.												
KF-S-1HB	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	10	90	V-0	All	-	
Single layer printed wiring boards.												
D	0.15 (0.006)	0.45 (0.018)	17 (0.67)	DS	50.8 (2.0)	288	10	105	V-0	-	-	
KF-D-4V0	0.10 (0.004)	0.30 (0.012)	17 (0.67)	DS	25.4 (1.0)	288	20	130	V-0	All	*	
KF-D-5V0	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	*	
KF-S-4V0	0.10 (0.004)	0.30 (0.012)	18 (0.71)	SS	254.0 (10.0)	288	5	130	V-0	All	*	

% - When the external copper thickness is in the range of 103-140mic, the minimum conductor width is 0.27mm and the minimum edge conductor width is 0.27mm.

* - CTI PLC is marked on individual board.

Marking: Company name or tradename "KINGFORD" , or file number and type designation and the Recognized Component Mark,  . May be followed by a suffix to denote factory identification or burning test classification.
Last Updated on 2015-04-03

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".